



SDS

GHS Safety Data Sheet PROFILE Products, LLC

Profile® Vegetative Overspray

MSDS Number: LIM049

Revision Date: 1/1/14

Page 1 of 5

1 PRODUCT AND COMPANY IDENTIFICATION

Manufacturer

PROFILE Products, LLC
750 LAKE COOK ROAD
SUITE 440
BUFFALO GROVE, IL 60089

Phone: (847) 215-1144
Fax: (847) 215-0577
Email: profileproducts.com
Web: www.profileproducts.com

Product Name: Profile® Vegetative Overspray
Revision Date: 1/1/14
MSDS Number: LIM049
CAS Number: Not applicable
Product Use: Erosion control mulch for hydraulic seeding

Product Description: Green dyed cellulose fibers from shredded waste paper sources

2 HAZARDS IDENTIFICATION

Route of Entry: Inhalation, skin contact, eye contact


Inhalation: Cellulose dust may cause sneezing, irritation, and dryness of the nose and throat. Dust may aggravate pre-existing respiratory conditions.

Skin Contact: Cellulose dust can cause irritation. Skin absorption is not known to occur.

Eye Contact: Cellulose dust can irritate the eyes.

Ingestion: No reports of human ingestion.

NFPA: Health = 1, Fire = 1, Reactivity = 0



OSHA Classification: Cellulose dust is a hazardous substance as defined by the Hazard Communication Standard 29CFR 1910.1200



SDS

GHS Safety Data Sheet PROFILE Products, LLC

Profile® Vegetative Overspray

MSDS Number: LIM049

Revision Date: 1/1/14

Page 2 of 5

3

COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients:

Cas #	Perc.	Chemical Name
-------	-------	---------------

N /A		Proprietary		Hydrocolloidal Based Polysaccharide Tackifier
9000300		Proprietary		Guar Gum

4

FIRST AID MEASURES

Inhalation:	Usually not a problem. Remove to fresh air if respiratory irritation develops, and get medical aid promptly if irritation persists.
Skin Contact:	Usually not a problem. Wash off with running water if irritation is experienced.
Eye Contact:	Open eyelids and flush with water.
Ingestion:	Get medical attention.

5

FIRE FIGHTING MEASURES

Flammability:	Combustible product
Flash Point:	Not applicable
Flash Point Method:	Not applicable
Autoignition Temp:	200-260°C (400-500°F)

Conditions to avoid: In contact with flames or hot surfaces

Flammable- Extinguish with water; same as a wood fire

6

ACCIDENTAL RELEASE MEASURES

Scoop up product. Wear goggles and respirator if dust is produced in unventilated areas. Wet product will be slippery.

7

HANDLING AND STORAGE

Handling Precautions:	Clean up areas where dust settles. Minimize blowdown or other practices that generate high airborne dust concentrations.
Storage Requirements:	Store in a cool, dry place. Keep away from sources of ignition.



SDS

GHS Safety Data Sheet PROFILE Products, LLC

Profile® Vegetative Overspray

MSDS Number: LIM049

Revision Date: 1/1/14

Page 3 of 5

8

EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls:

None required for outdoor mixing and application. Use dust collection system for indoor handling operations.

Personal Protective Equip:

Eye Protection: Wear goggles when emptying bags and during other operations where there is a risk of dust entering the eyes.

Gloves: Leather, plastic or rubber gloves could be worn to minimize skin irritation.

Respirators: When handling methods generate dust at concentrations that exceed occupational exposure limits, wear a NIOSH approved respirator. A fabric respirator or a facepiece respirator with dust cartridges will generally provide adequate protection.

Footwear: The product is slippery when wet. Wear appropriate footwear.

9

PHYSICAL AND CHEMICAL PROPERTIES

Appearance:

Dyed, green paper fibers - Shredded waste paper

Physical State:

Cellulose Fibers

Odor:

Mild wood odor

Spec Grav./Density:

Lighter than water

Vapor Pressure:

N/A

10

STABILITY AND REACTIVITY

Stability:

Stable product

Conditions to Avoid:

Contact with strong acids and oxidizers may generate heat. Product may ignite at temperatures in excess of 200°C (400°F).

Materials to Avoid:

Strong acids and oxidizers

Hazardous Polymerization:

Will not occur.

11

TOXICOLOGICAL INFORMATION

EFFECTS OF CHRONIC EXPOSURE:

Inhalation: Frequent and repeated exposure to wood dust is associated with an increased risk of developing nasal cancer.

Skin Contact: Although rare, wood dust may cause dermatitis in sensitized people.

Particulates Not Otherwise

Regulated (PNOR):

OSHA: PEL-TWA 15 mg/m³ (Total Dust);
5 mg/m³ (Respirable fraction)

Irritancy: Cellulose could be a mild irritant.

Sensitization: Some cellulose dusts may cause allergic skin reactions.



SDS

GHS Safety Data Sheet PROFILE Products, LLC

Profile® Vegetative Overspray

MSDS Number: LIM049

Revision Date: 1/1/14

Page 4 of 5

12

ECOLOGICAL INFORMATION

Guar Gum (CAS# 9000-30-0) is listed as an inert ingredient permitted for use in nonfood use pesticide products by EPA. It is also classified under the Federal Insecticide, Fungicide and Rodenticide Act (FIFRA) as a minimal risk inert substance (List 4A) meaning that as a pesticide, Guar Gum is considered by the EPA to pose little or no risk to humans or the environment. The US Department of Agriculture (USDA) National Organic Program (NOP) also allows the use of Guar Gum in a variety of applications, but primarily as a pesticide in organic production operations. Finally, Guar Gum is listed on the Generally Recognized as Safe (GRAS) list by the Food and Drug Administration (FDA).

48-hr LC₅₀ = >100% for Daphnia magna when runoff generated using ASTM D7101 (2"/hr rainfall rate) was tested according to EPA-821-R-02-012.

13

DISPOSAL CONSIDERATIONS

Normally can be disposed of as a wood residue. Ensure disposal is in compliance with local, provincial (state), and federal regulations.

14

TRANSPORT INFORMATION

DOT Class: Not regulated #



SDS

GHS Safety Data Sheet

PROFILE Products, LLC

Profile® Vegetative Overspray

MSDS Number: LIM049

Revision Date: 1/1/14

Page 5 of 5

15

REGULATORY INFORMATION

COMPONENT / (CAS/PERC) / CODES

*Guar Gum / (9000300 n/a%) / TSCA

REGULATORY KEY DESCRIPTIONS

MASS = MA Massachusetts Hazardous Substances List
NRC = Nationally Recognized Carcinogens
OSHA WAC = OSHA Workplace Air Contaminants
PA = PA Right-To-Know List of Hazardous Substances
TXAIR = TX Air Contaminants with Health Effects Screening Level

CERCLA = Superfund clean up substance
CSWHS = Clean Water Act Hazardous substances
EHS302 = Extremely Hazardous Substance
EPCRAWPC = EPCRA Water Priority Chemicals
HAP = Hazardous Air Pollutants
NJ EHS = NJ Extraordinarily Hazardous Substances
NJHS = NJ Right-to-Know Hazardous Substances
OSHA PSM = OSHA Chemicals Requiring process safety management
SARA 313 = SARA 313 Title III Toxic Chemicals

16

OTHER INFORMATION