

EcoBlend™ Wood Fiber/Cellulose Fiber

**Now with
TriFlo™!** — makes the best
hydraulic mulch even better!

- Improves moisture retention
- Improves the suspension of mulch, seed and fertilizer within the slurry and prevents the dewatering of the fiber mulch
- Improves the application of hydraulic mulch in a more uniform layer for better coverage and enhanced product performance
- Improves application efficiency by increasing shooting distance and enhancing hose performance—greatly reducing downtime associated with clogging



EcoBlend™ — The ultimate in blend performance!

Get more build out of every Eco bag

Profile's Thermally Refined® wood fibers maximize coverage and performance. Our processing technology produces fibers that hold 50% more water than competitive wood fiber products. Atmospherically refined wood fiber simply doesn't provide as much coverage per bag as the Eco line.

- EcoBlend™ is a combination of cellulose and premium wood fiber that absorbs water rapidly, forming a homogeneous slurry
- EcoBlend combines 30% cellulose fiber that ensures flexibility in pumping and spraying, while 70% wood fiber enhances turf coverage
- Delivers up to 15% greater coverage versus competitive blend products—an economical choice in blend products
- Provides greater yield and better loft compared to 100% cellulose
- Non-toxic and environmentally safe
- Maximum slope length of 23 feet
- EcoBlend functional longevity is ≤ 3 months



Product Composition:

Thermally Refined® Wood Fibers – 60%
 Cellulose Fiber (maximum) – 28%
 Moisture Content – 12% ± 3%
 (40) 50-lb bales per pallet

Slope Gradient/Condition

≤ 4H:1V
 > 4H:1V and ≤ 3H:1V

Rate

2000 lb/acre
 2500 lb/acre



PROFILE Products LLC · 750 Lake Cook Road · Suite 440 · Buffalo Grove, IL 60089

Technical Assistance: 800-508-8681

www.profileproducts.com