

EcoFibre® Premium Wood Fiber Mulch

**Now with
TriFlo™!** — makes the best
hydraulic mulch even better!

- Improves moisture retention
- Improves the suspension of mulch, seed and fertilizer within the slurry and prevents the dewatering of the fiber mulch
- Improves the application of hydraulic mulch in a more uniform layer for better coverage and enhanced product performance
- Improves application efficiency by increasing shooting distance and enhancing hose performance—greatly reducing downtime associated with clogging



EcoFibre® premium wood fiber covers the same area with 20-30% less product than cellulose mulch!

Get more build out of every Eco bag

Profile's Thermally Refined® wood fibers maximize coverage and performance. Our processing technology produces fibers that hold 50% more water than competitive wood fiber products. Atmospherically refined wood fiber simply doesn't provide as much coverage per bag as the Eco line.

- EcoFibre® is 100% Thermally Refined® wood fiber which results in higher water-holding capacity promoting faster and more complete germination
- Great soil bond to help prevent vegetation failure and callbacks
- Longer wood fibers provide better erosion control
- Non-toxic and environmentally safe
- Maximum slope length of 28 feet
- Use approved mechanically agitated equipment for optimum pumping and application performance
- EcoFibre functional longevity is ≤ 3 months



Product Composition:

Thermally Refined® Wood Fibers – 88% $\pm$ 3%
 Moisture Content – 12% $\pm$ 3%
 (40) 50-lb bales per pallet

Slope Gradient/Condition

$\leq 4H:1V$
 $> 4H:1V$ and $\leq 3H:1V$
 $> 3H:1V$ and $\leq 2H:1V$

Rate

2000 lb/acre
 2500 lb/acre
 3000 lb/acre

