

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 05/07/2020

Reviewed on 05/07/2020

* 1 Identification

- **Product Identifier**
- **Trade Name:** 20-0-20-SP
- **Relevant identified uses of the substance or mixture and uses advised against:**
- **Product Description:** Fertilizer
- **Details of the Supplier of the Safety Data Sheet:**
- **Manufacturer/Supplier:**
Florikan ESA, LLC
6801 Energy Ct. Suite 100
Sarasota, FL 34234
Ph: 941-379-4048 ext 332
Fax: 941-377-3633
Email product info: Doug Cabe; dcabe@florikan.com
- **Emergency telephone number:** Chemtrec 1-800-424-9300 or outside USA 1-703-527-3887

www.Florikan.com

2 Hazard(s) Identification

- **Classification of the substance or mixture:** Non-Regulated Material
- **Label elements:**
- **Hazard pictograms:** Non-Regulated Material
- **Signal word:** Non-Regulated Material
- **Hazard-determining components of labeling:**
Dolomitic limestone
Quartz (SiO₂)
- **Hazard statements:** Non-Regulated Material
- **Unknown acute toxicity:**
This value refers to knowledge of known, established toxicological or ecotoxicological values.
24.3 % of the mixture consists of component(s) of unknown toxicity.
- **Classification system:** NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme
- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**

HEALTH	0	Health = *0
FIRE	0	Fire = 0
REACTIVITY	0	Physical Hazard = 0

- **Hazard(s) not otherwise classified (HNOC):** None known

* 3 Composition/Information on Ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of substances listed below with non-hazardous additions.

· **Dangerous Components:**

CAS: 57-13-6	Urea	15-35%
RTECS: YR 6250000		

(Contd. on page 2)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 05/07/2020

Reviewed on 05/07/2020

Trade Name: 20-0-20-SP

CAS: 16389-88-1	Dolomitic limestone ⚠ Skin Irrit. 2, H315; STOT SE 3, H335; Eye Irrit. 2B, H320	15-35%
CAS: 14808-60-7 RTECS: VV 7330000	Quartz (SiO ₂) ⚠ Carc. 1A, H350; STOT RE 1, H372; ⚠ Acute Tox. 4, H332; STOT SE 3, H335; Eye Irrit. 2B, H320	≤2.5%

Additional information:

The exact percentages of the ingredients of this mixture are considered to be proprietary and are withheld in accordance with the provisions of paragraph (i) of §1910.1200 of 29 CFR 1910.1200 Trade Secrets.

* 4 First-Aid Measures

Description of first aid measures

General information: If symptoms persist, call a physician.

After inhalation: In case of unconsciousness place patient stably in the side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation occurs, consult a doctor.

After eye contact:

Rinse opened eye for at least 15 minutes under running water. If symptoms persist, consult a doctor.

If easy to do so, remove contact lenses if worn.

If eye irritation occurs, consult a doctor.

After swallowing: If swallowed and symptoms occur, consult a doctor.

Information for doctor

Most important symptoms and effects, both acute and delayed:

Quartz: Can cause silicosis, a fibrosis (scarring) of the lungs. Silicosis may be progressive; it may lead to disability and death; inhaled from occupational sources is classified as carcinogenic to humans. Some studies show in workers exposed to respirable quartz excess numbers of cases of scleroderma, connective tissue disorders, lupus, rheumatoid arthritis, chronic kidney diseases and end-stage kidney disease, chronic bronchitis and emphysema.

Indication of any immediate medical attention and special treatment needed:

No further relevant information available.

5 Fire-Fighting Measures

Extinguishing media

Suitable extinguishing agents: Use fire fighting measures that suit the environment.

For safety reasons unsuitable extinguishing agents: No further relevant information.

Special hazards arising from the substance or mixture: No further relevant information available.

Advice for firefighters

Special protective equipment for firefighters:

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

6 Accidental Release Measures

Personal precautions, protective equipment and emergency procedures: Not required.

Environmental precautions: No special measures required.

Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Dispose of the collected material according to regulations.

Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 3)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 05/07/2020

Reviewed on 05/07/2020

Trade Name: 20-0-20-SP

· Protective Action Criteria for Chemicals

· PAC-1:		
57-13-6	Urea	30 mg/m ³
14808-60-7	Quartz (SiO ₂)	0.075 mg/m ³
· PAC-2:		
57-13-6	Urea	280 mg/m ³
14808-60-7	Quartz (SiO ₂)	33 mg/m ³
· PAC-3:		
57-13-6	Urea	1,700 mg/m ³
14808-60-7	Quartz (SiO ₂)	200 mg/m ³

7 Handling and Storage

- **Handling**
- **Precautions for safe handling:** No special precautions are necessary if used correctly.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s):** No further relevant information available.

* 8 Exposure Controls/Personal Protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters:**
- **Components with occupational exposure limits:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the remaining constituents have no known exposure limits.

57-13-6 Urea	
WEEL	Long-term value: 10 mg/m ³
14808-60-7 Quartz (SiO₂)	
PEL	Long-term value: 0.05* mg/m ³ *resp. dust; 30mg/m ³ /%SiO ₂ +2
REL	Long-term value: 0.05* mg/m ³ *respirable dust; See Pocket Guide App. A
TLV	Long-term value: 0.025* mg/m ³ *as respirable fraction

- **Additional information:** The lists that were valid during the creation of this SDS were used as basis.
- **Exposure controls:**
- **Personal protective equipment**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing and wash before reuse.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.

(Contd. on page 4)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 05/07/2020

Reviewed on 05/07/2020

Trade Name: 20-0-20-SP

- **Breathing equipment:** Not required.
- **Protection of hands:**



Protective gloves

- **Material of gloves:**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material:**

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

- **Eye protection:**



Tightly sealed goggles

- **Limitation and supervision of exposure into the environment:** None

9 Physical and Chemical Properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form:

Granulate

Color:

Grayish

- **Odor:**

Slight

- **Odor threshold:**

Not determined.

- **pH-value:**

Not determined.

- **Change in condition**

Melting point/Melting range:

Not determined.

Boiling point/Boiling range:

≥1,500 °C (≥34.700 °F)

- **Flash point:**

None

- **Flammability (solid, gaseous):**

Not determined.

- **Ignition temperature:**

Not applicable

- **Decomposition temperature:**

Not determined.

- **Auto igniting:**

Product is not self-igniting.

- **Danger of explosion:**

Product does not present an explosion hazard.

- **Explosion limits:**

Lower:

Not determined.

Upper:

Not determined.

- **Vapor pressure:**

Not applicable.

- **Density @ 20 °C (68 °F):**

≥1.9479-≤1.949 g/cm³ (≥16.2552-≤16.2644 lbs/gal)

- **Relative density:**

Not determined.

- **Vapor density:**

Not applicable.

(Contd. on page 5)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 05/07/2020

Reviewed on 05/07/2020

Trade Name: 20-0-20-SP

- **Evaporation rate:** Not applicable.
- **Solubility in / Miscibility with:**
 - Water:** Soluble.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
 - Dynamic:** Not applicable.
 - Kinematic:** Not applicable.
- **Solvent content:**
 - VOC content:** 0.00 %
 - Solids content:** 100.0 %
- **Other information:** No further relevant information available.

10 Stability and Reactivity

- **Reactivity:** No further relevant information available.
- **Chemical stability:** Product is stable under normal conditions.
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions:** No dangerous reactions known.
- **Conditions to avoid:** No further relevant information available.
- **Incompatible materials:**

Urea reacts with calcium hypochlorite or sodium hypochlorite to form the explosive nitrogen trichloride.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological Information

- **Information on toxicological effects:**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

7447-40-7 Potassium Chloride

Oral	LD50	2,600 mg/kg (Rat)
------	------	-------------------

57-13-6 Urea

Oral	LD50	8,471 mg/kg (Rat)
------	------	-------------------

14808-60-7 Quartz (SiO₂)

Oral	LD50	>22,500 mg/kg (Rat)
		mg/kg (Rabbit)
Inhalative	LC50/96 hours	1,033 mg/l (Trout)

- **Primary irritant effect:**
- **On the skin:** Irritant to skin and mucous membranes.
- **On the eye:** Irritating effect.
- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
- **Carcinogenic categories:**
- **IARC (International Agency for Research on Cancer):**

"In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of

(Contd. on page 6)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 05/07/2020

Reviewed on 05/07/2020

Trade Name: 20-0-20-SP

chemicals to humans, Silica, silicate dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. May cause cancer. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled"

Group 1 - Carcinogenic to humans

Group 2A - Probably carcinogenic to humans

Group 2B - Possibly carcinogenic to humans

Group 3 - Not classifiable as to its carcinogenicity to humans

Group 4 - Probably not carcinogenic to humans

14808-60-7	Quartz (SiO ₂)	1
· NTP (National Toxicology Program):		
14808-60-7	Quartz (SiO ₂)	K
· OSHA-Ca (Occupational Safety & Health Administration):		
None of the ingredients are listed.		

12 Ecological Information

· Toxicity:

· Aquatic toxicity:

57-13-6 Urea

EC50 >10,000 mg/l (Daphnia)

14808-60-7 Quartz (SiO₂)

EC50 218 mg/l (Green algae)

· **Persistence and degradability:** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential:** No further relevant information available.

· **Mobility in soil:** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Do not allow undiluted product or product that has not been neutralized to reach ground water, water course or sewage system.

· **Results of PBT and vPvB assessment:**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects:** No further relevant information available.

13 Disposal Considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Observe all federal, state and local environmental regulations when disposing of this material.

· **Uncleaned packaging**

· **Recommendation:** Disposal must be made according to official regulations.

· **Recommended cleansing agent:** Water, if necessary with cleansing agents.

(Contd. on page 7)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 05/07/2020

Reviewed on 05/07/2020

Trade Name: 20-0-20-SP

14 Transport Information

- **UN-Number:**
- **DOT, ADR/ADN, IMDG, IATA** Non-Regulated Material
- **UN proper shipping name:**
- **DOT, ADR/ADN, IMDG, IATA** Non-Regulated Material
- **Transport hazard class(es):**
- **DOT, ADR/ADN, ADN, IMDG, IATA**
- **Class:** Non-Regulated Material
- **Packing group:**
- **DOT, ADR/ADN, IMDG, IATA** Non-Regulated Material
- **Environmental hazards:** Not applicable.
- **Special precautions for user:** Not applicable.
- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:** Not applicable.
- **UN "Model Regulation":** Non-Regulated Material

15 Regulatory Information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture:**
- **SARA (Superfund Amendments and Reauthorization):**

· **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients are listed.

· **TSCA (Toxic Substances Control Act):**

7447-40-7	Potassium Chloride	ACTIVE
57-13-6	Urea	ACTIVE
16389-88-1	Dolomitic limestone	ACTIVE
25791-96-2	Poly(oxypropylene) triol	ACTIVE
14808-60-7	Quartz (SiO ₂)	ACTIVE

· **Hazardous Air Pollutants**

None of the ingredients are listed.

· **California Proposition 65:**

· **Chemicals known to cause cancer:**

14808-60-7 Quartz (SiO₂)

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients are listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

· **New Jersey Right-to-Know List:**

14808-60-7 Quartz (SiO₂)

· **New Jersey Special Hazardous Substance List:**

14808-60-7 Quartz (SiO₂) CA

(Contd. on page 8)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 05/07/2020

Reviewed on 05/07/2020

Trade Name: 20-0-20-SP

· Pennsylvania Right-to-Know List:		
14808-60-7	Quartz (SiO ₂)	
· Pennsylvania Special Hazardous Substance List:		
None of the ingredients are listed.		
· Carcinogenic categories:		
· EPA (Environmental Protection Agency):		
57-13-6	Urea	II
· TLV (Threshold Limit Value established by ACGIH):		
14808-60-7	Quartz (SiO ₂)	A2
· NIOSH-Ca (National Institute for Occupational Safety and Health):		
14808-60-7	Quartz (SiO ₂)	
· GHS label elements Non-Regulated Material		
· Hazard pictograms: Non-Regulated Material		
· Signal word: Non-Regulated Material		
· Hazard-determining components of labeling:		
Dolomitic limestone		
Quartz (SiO ₂)		
· Hazard statements: Non-Regulated Material		
· National regulations:		
None of the ingredients are listed.		
· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.		

16 Other Information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

· **Date of last revision/ revision number:** 05/07/2020 / 1

· **Abbreviations and acronyms:**

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road
 ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 ACGIH: American Conference of Governmental Industrial Hygienists
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 NIOSH: National Institute for Occupational Safety and Health
 OSHA: Occupational Safety & Health Administration
 TLV: Threshold Limit Value
 PEL: Permissible Exposure Limit
 REL: Recommended Exposure Limit
 Acute Tox. 4: Acute toxicity – Category 4
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Irrit. 2B: Serious eye damage/eye irritation – Category 2B

(Contd. on page 9)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 05/07/2020

Reviewed on 05/07/2020

Trade Name: 20-0-20-SP

Carc. 1A: Carcinogenicity – Category 1A

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

· *** Data compared to the previous version altered.**SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106