

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/04/2015

Reviewed on 09/04/2015

### \* 1 Identification

- **Product identifier**
- **Trade name: 21-2-10-180-LND**
- **Relevant identified uses of the substance or mixture and uses advised against:**
- **Product description** PC12 Fertilizers
- **Details of the supplier of the safety data sheet:**
- **Manufacturer/Supplier:**  
Florikan ESA, LLC  
6801 Energy Ct.  
Suite 100  
Sarasota, FL. 34240  
ph: 941-379-4048 ext 332  
Fax: 941-377-3633  
Email product info: Doug Cabe; dcabe@florikan.com
- **Emergency telephone number:** Chemtrec 800-424-9300

www.Florikan.com

### \* 2 Hazard(s) identification

- **Classification of the substance or mixture:**



GHS08 Health hazard

Carc. 1A H350 May cause cancer.

STOT RE 1 H372 Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.



GHS07

Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2B H320 Causes eye irritation.

#### · **Label elements:**

#### · **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

#### · **Hazard pictograms:**



GHS07



GHS08

**Safety Data Sheet (SDS)**

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/04/2015

Reviewed on 09/04/2015

**Trade name: 21-2-10-180-LND****Signal word:** Danger**Hazard-determining components of labeling:**Quartz (SiO<sub>2</sub>)**Hazard statements:**

Causes skin and eye irritation.

May cause cancer.

Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.

**Precautionary statements:**

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear protective gloves.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).

If exposed or concerned: Get medical advice/attention.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

IF ON SKIN: Wash with plenty of water.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

**Unknown acute toxicity:**

5.8 % of the mixture consists of component(s) of unknown toxicity.

**Classification system:****NFPA ratings (scale 0 - 4)**

Health = 2

Fire = 0

Reactivity = 0

**HMIS-ratings (scale 0 - 4)**

Health = \*2

Fire = 0

Reactivity = 0

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/04/2015

Reviewed on 09/04/2015

- **Hazard(s) not otherwise classified (HNOC):** None known

### \* 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture: consisting of the following components.

#### • **Dangerous Components:**

|                                      |                                                                                                                             |        |
|--------------------------------------|-----------------------------------------------------------------------------------------------------------------------------|--------|
| CAS: 57-13-6<br>RTECS: YR 6250000    | Urea                                                                                                                        | 25-50% |
| CAS: 7783-20-2<br>RTECS: BS 4500000  | Ammonium Sulfate<br>☞ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335                                             | 2-12%  |
| CAS: 14808-60-7<br>RTECS: VV 7330000 | Quartz (SiO <sub>2</sub> )<br>☞ Carc. 1A, H350; STOT RE 1, H372; ☞ Acute Tox. 4, H332; STOT SE 3, H335; Eye Irrit. 2B, H320 | 2-12%  |
| CAS: 7783-28-0<br>RTECS: TB 9375000  | Diammonium phosphate<br>☞ Skin Irrit. 2, H315; Eye Irrit. 2B, H320                                                          | 2-12%  |
| CAS: 7487-88-9<br>RTECS: OM 4500000  | Magnesium Sulphate<br>☞ STOT SE 3, H335                                                                                     | ≤ 2.5% |
| CAS: 1309-48-4                       | Magnesium Oxide<br>☞ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335                                              | ≤ 2.5% |

**Trade name: 21-2-10-180-LND**

|                                     |                                                                                                                             |        |
|-------------------------------------|-----------------------------------------------------------------------------------------------------------------------------|--------|
| CAS: 7720-78-7<br>RTECS: NO 8510000 | iron(II) sulfate<br>☞ Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2A, H319                                          | ≤ 2.5% |
| CAS: 7704-34-9                      | Sulfur<br>☞ Skin Irrit. 2, H315; STOT SE 3, H335; Eye Irrit. 2B, H320; Combustible Dust                                     | ≤ 2.5% |
| CAS: 10034-96-5<br>RTECS: OP0893500 | Manganese(II) Sulfate Monohydrate<br>☞ STOT RE 2, H373; ☞ Aquatic Chronic 2, H411; ☞ STOT SE 3, H335; Aquatic Acute 2, H401 | ≤ 2.5% |

### \* 4 First-aid measures

- **Description of first aid measures:**
- **General information:**  
Symptoms of poisoning may occur after several hours; therefore medical observation is advised for at least 48 hours after the accident.
- **After inhalation:**  
Consult a doctor for complaints.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:**  
Immediately wash with water and soap and rinse thoroughly.  
If skin irritation occurs, consult a doctor.
- **After eye contact:**  
Rinse opened eye for at least 15 minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If swallowed and symptoms occur, consult a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed:**  
Quartz: Can cause silicosis, a fibrosis (scarring) of the lungs. Silicosis may be progressive; it may lead to disability and death; inhaled from occupational sources is classified as carcinogenic to humans. Some studies show in workers exposed to respirable quartz excess numbers of cases of scleroderma, connective tissue disorders, lupus, rheumatoid arthritis, chronic kidney diseases and end-stage kidney disease, chronic bronchitis and emphysema.
- **Indication of any immediate medical attention and special treatment needed:**  
No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media:**

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/04/2015

Reviewed on 09/04/2015

Trade name: 21-2-10-180-LND

· **Suitable extinguishing agents:**

CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **Special hazards arising from the substance or mixture:** No further relevant information available.

· **Advice for firefighters:**

· **Protective equipment:**

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

### \* 6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures:** Not required.

· **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Dispose contaminated material as waste according to section 13.

Dispose of the collected material according to regulations.

· **Reference to other sections:**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### \* 7 Handling and storage

· **Handling**

· **Precautions for safe handling:** No special precautions are necessary if used correctly.

· **Information about protection against explosions and fires:** No special measures required.

· **Conditions for safe storage, including any incompatibilities:**

· **Storage**

· **Requirements to be met by storerooms and receptacles:** No special requirements.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:** No further relevant information available..

· **Specific end use(s):** No further relevant information available.

### \* 8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see section 7.

· **Control parameters:**

· **Components with occupational exposure limits:**

**57-13-6 Urea**

WEEL Long-term value: 10 mg/m<sup>3</sup>

**7783-20-2 Ammonium Sulfate**

PEL Short-term value: 10 mg/m<sup>3</sup>

Long-term value: 15 mg/m<sup>3</sup>

**14808-60-7 Quartz (SiO<sub>2</sub>)**

PEL Long-term value: 0.1 mg/m<sup>3</sup>

REL Long-term value: 0.05\* mg/m<sup>3</sup>

\*respirable dust; See Pocket Guide App. A

TLV Long-term value: 0.025\* mg/m<sup>3</sup>

\*as respirable fraction

**1309-48-4 Magnesium Oxide**

PEL Long-term value: 15\* mg/m<sup>3</sup>  
fume; \*total particulate

TLV Long-term value: 10\* mg/m<sup>3</sup>  
\*as inhalable fraction

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/04/2015

Reviewed on 09/04/2015

### 7720-78-7 iron(II) sulfate

|     |                                               |
|-----|-----------------------------------------------|
| REL | Long-term value: 1 mg/m <sup>3</sup><br>as Fe |
| TLV | Long-term value: 1 mg/m <sup>3</sup><br>as Fe |

· **Additional information:** The lists that were valid during the creation of this SDS were used as basis.

· **Exposure controls:**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing and wash before reuse.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· **Breathing equipment:** Not required.

· **Protection of hands:**

**S** Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Select glove material based on penetration times, rates of diffusion and degradation.

· **Material of gloves:**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material:**

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

· **Eye protection:**

**R** Tightly sealed goggles

## \* 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:

Granulate

Color:

Whitish

· **Odor:**

Slight

· **Odor threshold:**

Not determined.

· **pH-value:**

Not applicable.

· **Change in condition**

Melting point/Melting range:

Not determined.

Boiling point/Boiling range:

445 °C (833 °F)

· **Flash point:**

None

· **Flammability (solid, gaseous):**

Not determined.

· **Ignition temperature:**

Decomposition temperature:

Not determined.

· **Auto igniting:**

Product is not self-igniting.

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/04/2015

Reviewed on 09/04/2015

Trade name: 21-2-10-180-LND

- **Explosion limits:**
  - Lower:** Not determined.
  - Upper:** Not determined.
- **Vapor pressure:** Not applicable.
- **Density:**
  - Relative density:** Not determined.
  - Vapor density:** Not applicable.
  - Evaporation rate:** Not applicable.
- **Solubility in / Miscibility with:**
  - Water:** Soluble.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
  - Dynamic:** Not applicable.
  - Kinematic:** Not applicable.
- **Solvent content:**
  - Organic solvents:** 0.0 %
- **Other information:** No further relevant information available.

### 10 Stability and reactivity

- **Reactivity:** No further relevant information available.
- **Chemical stability:** Stable under normal conditions.
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions:** No dangerous reactions known.
- **Conditions to avoid:** No further relevant information available.
- **Incompatible materials:** Contact with fluorine, oxygen difluoride, and chlorine trifluoride will cause fire.
- **Hazardous decomposition products:** No dangerous decomposition products known.

### \*11 Toxicological information

- **Information on toxicological effects:**
- **Acute toxicity:**
- **LD/LC50 values that are relevant for classification:**

#### 57-13-6 Urea

|      |      |                  |
|------|------|------------------|
| Oral | LD50 | 8471 mg/kg (rat) |
|------|------|------------------|

#### 7783-20-2 Ammonium Sulfate

|            |               |                       |
|------------|---------------|-----------------------|
| Oral       | LD50          | 2840 mg/kg (rat)      |
| Inhalative | LC50/96 hours | 36.7 mg/l (Trout)     |
|            |               | 433 mg/l (Water flea) |

#### 14808-60-7 Quartz (SiO<sub>2</sub>)

|            |               |                   |
|------------|---------------|-------------------|
| Inhalative | LC50/96 hours | 1033 mg/l (Trout) |
|------------|---------------|-------------------|

#### 7783-28-0 Diammonium phosphate

|        |      |                   |
|--------|------|-------------------|
| Oral   | LD50 | >5000 mg/kg (rat) |
| Dermal | LD50 | >5000 mg/kg (rat) |

#### 7487-88-9 Magnesium Sulphate

|      |      |                   |
|------|------|-------------------|
| Oral | LD50 | >2000 mg/kg (rat) |
|------|------|-------------------|

(Contd. on page 7)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/04/2015

Reviewed on 09/04/2015

**Trade name: 21-2-10-180-LND**

|                                   |                        |
|-----------------------------------|------------------------|
| Inhalative LC50/4 h               | >2000 mg/l (rabbit)    |
| LC50/96 hours                     | 2820 mg/l (Pimephales) |
| <b>7720-78-7 iron(II) sulfate</b> |                        |
| Oral LD50                         | 1520 mg/kg (mouse)     |

• **Primary irritant effect:**

• **On the skin:** Irritant to skin and mucous membranes.

• **On the eye:** Irritating effect.

• **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

• **Carcinogenic categories:**

• **IARC (International Agency for Research on Cancer):**

Group 1 - Carcinogenic to humans

Group 2A - Probably carcinogenic to humans

Group 2B - Possibly carcinogenic to humans

Group 3 - Not classifiable as to its carcinogenicity to humans

Group 4 - Probably not carcinogenic to humans

"In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicate dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. May cause cancer. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled"

|                                                                     |                            |   |
|---------------------------------------------------------------------|----------------------------|---|
| 14808-60-7                                                          | Quartz (SiO <sub>2</sub> ) | 1 |
| • <b>NTP (National Toxicology Program):</b>                         |                            |   |
| 14808-60-7                                                          | Quartz (SiO <sub>2</sub> ) | K |
| • <b>OSHA-Ca (Occupational Safety &amp; Health Administration):</b> |                            |   |
| None of the ingredients are listed.                                 |                            |   |

### \*12 Ecological information

• **Toxicity:**

• **Aquatic toxicity:**

**57-13-6 Urea**

EC50 >10000 mg/l (daphnia)

**14808-60-7 Quartz (SiO<sub>2</sub>)**

EC50 218 mg/l (Green algae)

**7487-88-9 Magnesium Sulphate**

EC50 2700 mg/l (Green algae)

(Contd. on page 8)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/04/2015

Reviewed on 09/04/2015

Trade name: 21-2-10-180-LND

343.56 mg/l (Water flea)

- **Persistence and degradability:** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential:** No further relevant information available.
- **Mobility in soil:** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Do not allow undiluted product or product that has not been neutralized to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment:**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects:** No further relevant information available.

### \* 13 Disposal considerations

- **Waste treatment methods:**
- **Recommendation:**  
Observe all federal, state and local environmental regulations when disposing of this material.  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

### \* 14 Transport information

- **UN-Number:**
- **DOT, ADR, ADN, IMDG, IATA** Non-Regulated Material
- **UN proper shipping name:**
- **DOT, ADR, ADN, IMDG, IATA** Non-Regulated Material
- **Transport hazard class(es):**
- **DOT, ADR, ADN, IMDG, IATA**
- **Class:** Non-Regulated Material
- **Packing group:**
- **DOT, ADR, IMDG, IATA** Non-Regulated Material
- **Environmental hazards:** Not applicable.
- **Special precautions for user:** Not applicable.
- **Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:** Not applicable.
- **UN "Model Regulation":** Non-Regulated Material

### \* 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture:**
- **SARA (Superfund Amendments and Reauthorization):**

#### · Section 355 (extremely hazardous substances):

7720-78-7 iron(II) sulfate

#### · Section 313 (Specific toxic chemical listings):

7783-20-2 Ammonium Sulfate

11129-60-5 Manganese oxide

(Contd. on page 9)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/04/2015

Reviewed on 09/04/2015

**Trade name: 21-2-10-180-LND**

|                                                                      |                                   |          |
|----------------------------------------------------------------------|-----------------------------------|----------|
| 10034-96-5                                                           | Manganese(II) Sulfate Monohydrate |          |
| 7758-99-8                                                            | Copper Sulfate Pentahydrate       |          |
| 7733-02-0                                                            | Zinc Sulphate (anhydrous)         |          |
| 1314-13-2                                                            | Zinc Oxide                        |          |
| · <b>TSCA (Toxic Substances Control Act):</b>                        |                                   |          |
| 57-13-6                                                              | Urea                              |          |
| 7783-20-2                                                            | Ammonium Sulfate                  |          |
| 14808-60-7                                                           | Quartz (SiO2)                     |          |
| 7783-28-0                                                            | Diammonium phosphate              |          |
| 7447-40-7                                                            | Potassium Chloride                |          |
| 25791-96-2                                                           | Poly(oxypropylene) triol          |          |
| 7487-88-9                                                            | Magnesium Sulphate                |          |
| 1317-61-9                                                            | Iron Oxide                        |          |
| 1309-48-4                                                            | Magnesium Oxide                   |          |
| 7720-78-7                                                            | iron(II) sulfate                  |          |
| 7704-34-9                                                            | Sulfur                            |          |
| 1332-58-7                                                            | Kaolin                            |          |
| 7758-99-8                                                            | Copper Sulfate Pentahydrate       |          |
| 7733-02-0                                                            | Zinc Sulphate (anhydrous)         |          |
| 1314-13-2                                                            | Zinc Oxide                        |          |
| · <b>California Proposition 65:</b>                                  |                                   |          |
| · <b>Chemicals known to cause cancer:</b>                            |                                   |          |
| 14808-60-7                                                           | Quartz (SiO2)                     |          |
| · <b>Chemicals known to cause reproductive toxicity for females:</b> |                                   |          |
| None of the ingredients are listed.                                  |                                   |          |
| · <b>Chemicals known to cause reproductive toxicity for males:</b>   |                                   |          |
| None of the ingredients are listed.                                  |                                   |          |
| · <b>Chemicals known to cause developmental toxicity:</b>            |                                   |          |
| None of the ingredients are listed.                                  |                                   |          |
| · <b>Carcinogenic categories:</b>                                    |                                   |          |
| · <b>EPA (Environmental Protection Agency):</b>                      |                                   |          |
| 57-13-6                                                              | Urea                              | II       |
| 11129-60-5                                                           | Manganese oxide                   | D        |
| 10034-96-5                                                           | Manganese(II) Sulfate Monohydrate | D        |
| 7733-02-0                                                            | Zinc Sulphate (anhydrous)         | D, I, II |
| 1314-13-2                                                            | Zinc Oxide                        | D, I, II |
| · <b>TLV (Threshold Limit Value established by ACGIH):</b>           |                                   |          |
| 14808-60-7                                                           | Quartz (SiO2)                     | A2       |
| 1309-48-4                                                            | Magnesium Oxide                   | A4       |
| 1332-58-7                                                            | Kaolin                            | 2 mg/m3  |

(Contd. on page 10)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/04/2015

Reviewed on 09/04/2015

**Trade name: 21-2-10-180-LND**

· **NIOSH-Ca (National Institute for Occupational Safety and Health):**

14808-60-7 Quartz (SiO<sub>2</sub>)

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms:**



GHS07 GHS08

· **Signal word:** Danger

· **Hazard-determining components of labeling:**

Quartz (SiO<sub>2</sub>)

· **Hazard statements:**

Causes skin and eye irritation.

May cause cancer.

Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.

· **Precautionary statements:**

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear protective gloves.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).

IF exposed or concerned: Get medical advice/attention.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

IF ON SKIN: Wash with plenty of water.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

The product is subject to be classified according with the latest version of the regulations on hazardous substances.

· **State Right to Know:**

|                                      |                                                                                                                             |        |
|--------------------------------------|-----------------------------------------------------------------------------------------------------------------------------|--------|
| CAS: 57-13-6<br>RTECS: YR 6250000    | Urea                                                                                                                        | 25-50% |
| CAS: 7783-20-2<br>RTECS: BS 4500000  | Ammonium Sulfate<br>☞ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335                                             | 2-12%  |
| CAS: 14808-60-7<br>RTECS: VV 7330000 | Quartz (SiO <sub>2</sub> )<br>☞ Carc. 1A, H350; STOT RE 1, H372; ☞ Acute Tox. 4, H332; STOT SE 3, H335; Eye Irrit. 2B, H320 | 2-12%  |
| CAS: 7783-28-0<br>RTECS: TB 9375000  | Diammonium phosphate<br>☞ Skin Irrit. 2, H315; Eye Irrit. 2B, H320                                                          | 2-12%  |

(Contd. on page 11)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/04/2015

Reviewed on 09/04/2015

**Trade name: 21-2-10-180-LND**

|                             |                        |       |
|-----------------------------|------------------------|-------|
|                             | Polyurethane elastomer | 2-12% |
| CAS: 7447-40-7              | Potassium Chloride     | 2-12% |
| All ingredients are listed. |                        |       |

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

· **Date of preparation / last revision:** 09/04/2015 / 1

· **Abbreviations and acronyms:**

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road  
 ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
 IMDG: International Maritime Code for Dangerous Goods  
 DOT: US Department of Transportation  
 IATA: International Air Transport Association  
 ACGIH: American Conference of Governmental Industrial Hygienists  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 NFPA: National Fire Protection Association (USA)  
 HMIS: Hazardous Materials Identification System (USA)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 PBT: Persistent, Bioaccumulative and Toxic  
 vPvB: very Persistent and very Bioaccumulative  
 Acute Tox. 4: Acute toxicity, Hazard Category 4  
 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2  
 Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A  
 Eye Irrit. 2B: Serious eye damage/eye irritation, Hazard Category 2B  
 Carc. 1A: Carcinogenicity, Hazard Category 1A  
 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3  
 STOT RE 1: Specific target organ toxicity - Repeated exposure, Hazard Category 1  
 STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2  
 Aquatic Acute 2: Hazardous to the aquatic environment - AcuteHazard, Category 2  
 Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

· **\* Data compared to the previous version altered.**

SDS created by MSDS Authoring Services    www.msdsauthoring.com    +1-877-204-9106